



## 3200 Series Tripod Jack 5 Ton Capacity (4.5 tonnes)



### Standard High Quality Features:

- Steel Reservoir
- Quick rising threaded extension screw with steel lock nut
- Durable powder coat finish
- Tilt and roll mobility

### Standard Tests:

- Jack is set to relieve at 110% of rated load
- Structurally tested at a 150% of rated load

### Seal Kits:

- Pump/Reservoir – 324-V-31
- Ram/Cylinder – 324-3200K

The four 3200 Series jacks are designed around a common cylinder, pump and reservoir configuration that is compatible with four tripods. The cylinder, pump and reservoir can be removed from one 3200 Series tripod and installed in another, allowing four roll under heights.

All jacks in the 3200 Series are constructed “better than they have to be”, and rigorously tested.

### SPECIFICATIONS

P/N	Capacity		Roll Under		Hydraulic Lift		Extension Screw		Total Height	
	(tons)	(tonnes)	(")	(mm)	(")	(mm)	(")	(mm)	(")	(mm)
3200	5	4.5	11	279	12	305	3	76	26	660
3201	5	4.5	16	406	12	305	3	76	31	787
3202	5	4.5	20	508	12	305	3	76	35	889
3203	5	4.5	24	610	12	305	3	76	39	991